

Capabilities



Bars

| | |
|----------------------------|---|
| Rounds | 1/8" (.125) through 1" (Expanding to 1 1/4" in 2024) |
| Hexagons | 5/32" (.156) through 5/8" (.625) (Expanding to 1" in 2024) |
| Squares | 3/16" (.187) through 1/2" (.500) (Expanding to 3/4" in 2024) |
| Stainless Steel | 3/16" (.187) through 1/2" (.500) (Expanding to 1 1/4" in 2024) |
| Hot Roll Straighten | 3/16" (.187) through 3/4" (.750) |
| Lengths | Up to 20' |
| Tolerances | Max Carbon Range 0.28% or Less: .002" Total Max Carbon Range over 0.28% to 0.55% - .003" Total Restricted Tolerances – Please Inquire |
| Chamfering | Please inquire |

Wire

| | |
|-------------------|--|
| Diameter | 1/16" (.062) through 1" |
| Types | Bright Basic, Plating Quality, Cold Heading Quality |
| Carriers | 2,000# to 4,000# |
| Tolerances | Standard +/- .002" Restricted Tolerances – Please Inquire |

Grades

| | |
|------------------|--|
| Carbon | 1018, 1045, 1117, 1141, 1144, 1215, 12L14 |
| Alloy | 4140 LP Anneal, 4340 LP Anneal, 8620 |
| Stainless | 303, 304, 316, 410, 17-4 Inquire on Grades not Listed |

Additional Services

Pickle & Lime

De-Magnetizing