

# Capabilities



## Bars

<b>Rounds</b>	1/8" (.125) through 1" (Expanding to 1 1/4" in 2024)
<b>Hexagons</b>	5/32" (.156) through 5/8" (.625) (Expanding to 1" in 2024)
<b>Squares</b>	3/16" (.187) through 1/2" (.500) (Expanding to 3/4" in 2024)
<b>Stainless Steel</b>	3/16" (.187) through 1/2" (.500) (Expanding to 1 1/4" in 2024)
<b>Hot Roll Straighten</b>	3/16" (.187) through 3/4" (.750)
<b>Lengths</b>	Up to 20'
<b>Tolerances</b>	Max Carbon Range 0.28% or Less: .002" Total Max Carbon Range over 0.28% to 0.55% - .003" Total Restricted Tolerances – Please Inquire
<b>Chamfering</b>	Please inquire

## Wire

<b>Diameter</b>	1/16" (.062) through 1"
<b>Types</b>	Bright Basic, Plating Quality, Cold Heading Quality
<b>Carriers</b>	2,000# to 4,000#
<b>Tolerances</b>	Standard +/- .002" Restricted Tolerances – Please Inquire

## Grades

<b>Carbon</b>	1018, 1045, 1117, 1141, 1144, 1215, 12L14
<b>Alloy</b>	4140 LP Anneal, 4340 LP Anneal, 8620
<b>Stainless</b>	303, 304, 316, 410, 17-4 Inquire on Grades not Listed

## Additional Services

Pickle & Lime

De-Magnetizing