

# Capabilities



## Bars

<b>Rounds</b>	1/8" (.125) through 1 1/4" (1.25)
<b>Hexagons</b>	5/32" (.156) through 1"
<b>Squares</b>	1/8" (.125) through 3/4" (.750)
<b>Hot Roll Straighten</b>	3/16" (.187) through 1"
<b>Lengths</b>	Up to 20'
<b>Tolerances</b>	Max Carbon Range 0.28% or Less: .002" Total
	Max Carbon Range over 0.28% to 0.55% - .003" Total
	Restricted Tolerances – Please Inquire
<b>Chamfering</b>	Rounds 1/2" (.500) and Larger

## Wire

<b>Diameter</b>	1/16" (.062) through 1"
<b>Types</b>	Bright Basic, Plating Quality, Cold Heading Quality
<b>Carriers</b>	2,000# to 4,000#
<b>Tolerances</b>	Standard +/- .002"
	Restricted Tolerances – Please Inquire

## Grades

<b>Carbon</b>	1018, 1045, 1117, 1141, 1144, 1215, 12L14
<b>Alloy</b>	4140 LP Anneal, 4340 LP Anneal, 8620
	Inquire on Grades not Listed

## Additional Services

<b>Pickle &amp; Lime</b>
<b>De-Magnetizing</b>